

ETNC24-FC-PIR-BAC-01



Wall-mount, 24VAC thermostat, for Fan-Coil applications with integrated Passive IR (PIR) Occupancy Sensor and BACNET B.M.S. interface

The ETNC24-FC-PIR-BAC-01 is an advanced, energy saving thermostat suitable for hotel rooms and offices controlling the Fan Coil.

The thermostat offers various configurations, either Cool/Heat/Auto/Fan, or alternatively Cool Only or Heat Only, all of which are selectable with 1, 2 or 3 fan speed control.





























The thermostat can be adjusted to the field configuration either from the BMS or by DIP Switches and simple Technician Settings interface using the buttons and LCD display.

All these qualities make the ETNC24-FC-PIR-BAC-01 suitable for wholesalers, keeping a stock on the shelf and supplying the proper configuration according to cistomers' specifications as well as for the technicians who can use it for various applications.

Features

- Wall mount, 24VAC thermostat
- Modes: Cool/Heat/Fan only/Auto
- Fan speeds: 1, 2 or 3 + Auto speed
- Economy mode + Sleep mode + Set point limits
- Window contact normally open/normally close -DIP switch selectable
- Internal/external sensor DIP switch selectable
- · Auto fan fan on demand
- 2 pipe or 4 pipe Fan coil control

- Integrated Occupancy Sensor (PIR)
- BACNET/MSTP interface
- · Lock buttons option
- Energy saving cost efficient, environmental friendly thermostat
- · Celsius or Fahrenheit temperature scales
- IR option
- Freeze protection
- · Filter counter and Alarm

Applications

2 pipe				
4 pipe				
Cool Valve and Elect. Heater				
2 nd stage Elect. Heater				
1 st stage Radiator Heating				
2 nd stage F/C Heating				
Chilled beam				

Wiring diagram

11	_	Fan high			
12	_		ndoor fan (0.5A) , 2 or 3 speeds		
13	_	Fan low	1, 2 0. 0 opcodo		
14	-	Heat element (0.5A)			
IN	-	Contact input / E	external PIR /		
0	ļ_	T2 Change over sensor / T3 Soft start sensor			
В	-	Communication RS 485 BACnet protocol			
Α	_				
0	_		nsor / T3 Soft start sensor /		
T1	_	Door switch			
15	_	Cool valve (4P) / Cool/Heat valve (2P) (0.5A) Heat valve (4P) (0.5A)			
16	_				
С	_	Main aunaly 24)	24\/AC		
R	<u> </u>	Main supply 24	VAC		



ETNC24-FC-PIR-BAC-01

ETN

Wall mount thermostat/panel 24VAC, 12VDC



Colors



white silver black gold others

Accessories

|--|

Specifications

Color	white, silver, black, others	Temperature Input	50k@25ºc
Scale	°C / °F	Flammability	UL94V-0
Weight	0.25 Kg	Plastic	PC/ABS
Temperature Range	10°C ÷ 30°C, 50°C ÷ 86°F	Accuracy	±1°C



